

Circular saw MiniMax SC3 Classic

MiniMax SC3 Classic circular saw for professional use. Heavy-duty steel frame. Table made of cast iron. The saw blade is raised and lowered via screw spindles and handwheels, and tilts up to 45° for mitre cutting. Adjustment via a clear, easy-to-read scale. Integrated aluminium sliding table with telescopic fence rail and a "flip-over" stop for repetitive work, including a clamping device. Rip capacity with fence max. 900 mm. Max. saw blade diameter 315 mm and with scoring blade (optional) max. 250 mm. Standard motor 5 kW S6.

Equipped with safety devices in accordance with CE regulations and supplied with a CE Declaration of Conformity.

See accessories below.

School equipment:

brake start package (incl. preparation for Lupax start permission unit) and overhead blade guard

Optional accessories:

- extended sliding table, 2660 mm
- rip fence with digital display
- scoring unit incl. 80 mm blade (factory installed)
- right-side extension table, enabling 1270 mm rip capacity
- additional support for large panels
- mitre cutting unit



Skolustrustning: överarmskydd



Skolustrustning: startapparat

Technical data

Cast iron table	560 x 840	mm
Sliding table	270 x 2250 (2660)	mm
Max squaring stroke of sliding table	2310 (2800)	mm
Motor S6 (option)	5,0	kW
Sawblade (max. with scoring unite)	250-315 (250)	mm
Sawblade projection from table at 90°	100	mm
Sawblade projection from table at 45°	79	mm
Sawblade arbor size	30	mm
Sawblades tilting	0-45	°
Sawblades speed	4000	1/mm
Exhaust hoods diameter at the base	120	mm
Exhaust hoods diameter on overhead protection	80	mm
Cutting width on parallel fence (with extensiontable, option)	900 (1270)	mm