

## Column drilling machine A2608T

1925009

Easy to operate vertical drilling machines, mounted on a sturdy steel column. Drill head and drill arm can be swung through 360° and raised and lowered using a gear rack. Gear operation and gearbox with helical gears made of steel and fibre material for a silent machine requiring minimum maintenance. Quick and easy selection between the 8 stages in the gearbox.

Supplied complete with motor protection with zero voltage release and emergency stop – IP54, integrated drift for easy tool changes, rectangular table with T-slots, oil channel and drill guard with microswitch. The machine is equipped with a reversing spindle as standard.

All speeds are based on 50Hz.

**A 2608 T** is designed for premises which demand a high safety classification, for example, woodworking rooms.

**School equipment:** drillchuck with arbor, telescopic chuck guard incl microswitch, DMK-starter incl push button enclosure, prepared for Lupax.

**Optionals:** Lupax start-up premission, machine vices, quick clamps, coordinate tables, drill bits etc. – request a quote!



### Technical data

Feed	Manual
Motor effect - voltage	0,75 / 0,95 kW - 400 V / 3-phase
Drill capacity in steel	25 mm
Thread capacity	16 M
Spindle movement	135 mm
Spindle nose	MK 3
Spindle speed	105-2900 r/min
T-slot c/c	140 mm
T-slot width, bench	14 mm
Column diameter	100 mm
Table	400 x 500 mm
Weight	180 kg